

EH 9 BLM magic Electric Breaker, 115V, SDS-max

Item Number: 0008739

EH 9 BLM magic

Maintenance-free time is money!

>> The innovative magic drilling and chiseling hammers save money because they lose no time due to maintenance and failures: The three-phase AC motor means that there is no changing of worn-out carbon brushes. Failures due to burnt-out windings in the rotor of the motor are likewise a thing of the past. On the other hand, the built-in frequency inverter is a very useful feature, since it means that magic electric hammers can be plugged in to a standard mains socket. <<



Additional Advantages

- No wear at all: non-contact rpm setting.
- Consistent and concentrated performance in hard and soft materials due to the new high-tech percussion system.
- Undoubtedly safer operation for the user due to the unique built-in converter: automatic voltage-matching protects against under- and over-voltages.
- The work becomes less tiring thanks to the individually adjustable Pro-Ergo® handle system: Quick and easy shifting of the holding position during the work means more can be done in the same time. Naturally, we also offer a standard handle by request.
- Optionally can be equipped with SDS-max (BLM) or hexagonal tool shank (BL).

Description	Metric	Imperial
L x w x h (without tool)	620 x 105 x 245 mm	24.4 x 4.1 x 9.6 in
Weight without tool	10.7 kg	23.6 lb
Shank	SDS-max mm	SDS-max in
Percussion rate (adjustable)	1300 - 2150 1/min	1300 - 2150 blows/min
Single stroke impact	19 (1,9) J (mkp)	14 ft lb/blow
Demolition performance	630 kg/h	1390 lb/h
Drive engine	three-phase induction motor with inverter in series for alternating current 50/60 Hz with protective insulation	
Voltage	110 - 127 1~ V	110 - 127 1~ V
Rated current	13 A	13 A
Power draw (required generator output: 3,3 kW)	1.2 kW	1.6 hp
Percussion system	air-cushioned percussion system	
Sound power level conforming to EC guideline 84/537/EEC	94 dB(A)	94 dB(A)

Standard Package - EH 9 BLM magic

incl. 5 m supply cable, non-jamming chisel, injection-moulded carrycase with tool compartments, grease gun with 180 cm³ grease, instruction book and EC-Conformity Certificate

Please refer to our Price List and Ordering Guide for complete accessory information.

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

Generated on Wednesday, April 6, 2011

